



WIG STAND

Based on a photo in MWG Keen Edge

Wig Stand Head




Start with a blank of lightweight wood 150 square by 110mm thick. This can be held as a square in a large chuck, or on a faceplate with wide-spaced screws, or by a chuck in a drilled dovetail. Flatten the face that is to be the underside. Make a dovetail to fit a 25mm chuck by 15mm deep (Drill a 26mm dia hole). This will also be the dovetail to fit the shaft of the wig stand. Or you may drill an additional hole to remount this on a long screw chuck. Or you may cut a spigot around the 26mm hole. Sand and finish this underside.




Turn the wood around and re-mount it on a 25mm chuck or long screw chuck or 50mm chuck. Round off the top of the wig stand. The upper half of this top is almost a hemisphere curving into almost straight sides for the lower half. This should now be about 140mm diameter and 100mm high. Sand and finish. Non-drying oil and wax finishes are not recommended but drying oils, polyurethane or lacquer may be used.

The Base




Start with a block of heavy wood about 160mm square and 50mm thick.

Mount this on a screw chuck or use a shallow drilled dovetail. Flatten the bottom (not concave) and make a shallow dovetail to fit a 50mm chuck. Finish this surface now if the chuck dovetail is not being removed as detailed below.




Turn the wood over and remount on a chuck using the dovetail. Round the wood off. Make the very top of the curve into a flat or slight concave where the shaft will fit. Make a dovetail to fit a 25mm chuck by 15mm deep (Drill a 26mm dia hole). This will also be the dovetail to fit the shaft of the wig stand.

You may add beads and decoration to this surface. Sand and finish.



You may now declare the base to be "finished" or turn the wood over and remount on a 25mm chuck or jam chuck. Cut the bottom to a slight concave to remove the chuck dovetail. Sand and finish.

The Shaft



Start with a piece at least 240mm long and about 40mm square. Place it between centers. Make a 26mm diameter by 14mm long spigot on each end. Turn the remainder to a shape of your choice.

