



## **WIG STAND**

Starting on a screw chuck


## Wig Stand Head



Start with a blank of lightweight wood 150 square by 110mm thick. Mount this on a screw chick set in the side that is to be the underside of the wig stand head. Turn a spigot for a 50mm chuck on the top side of the head.




Make a dovetail to fit a 25mm chuck by 15mm deep (Drill a 26mm dia hole). This will also be the dovetail to fit the shaft of the wig stand. Or you may cut a spigot around the 26mm hole. Sand and finish this underside.




Turn the wood around and mount it on a 25mm or a 50mm chuck. Round off the top of the wig stand. The upper half of this top is almost a hemisphere curving into almost straight sides for the lower half. This should now be about 140mm diameter and 100mm high. Sand and finish. Non-drying oil and wax finishes are not recommended but use drying oils, polyurethane or lacquer.

## The Base



Start with a block of heavy wood about 160mm square and 50mm thick. Mount this on a screw chuck or use a shallow drilled dovetail. Flatten the bottom (not concave) and make a shallow dovetail to fit a 50mm chuck. Finish this surface now if the chuck dovetail is not being removed as detailed below.



You may now declare the base to be "finished" or turn the wood over and remount on a 25mm chuck or jam chuck. Cut the bottom to a slight concave to remove the chuck dovetail. Sand and finish.





Start with a piece at least 240mm long and about 40mm square. Place it between centers. Make a 26mm diameter by 14mm long spigot on each end. Turn the remainder to a shape of your choice.

